



3.0m/10ft Class 3 Dual Polarized Microwave Parabolic Antenna 13.25 Ghz

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Famous
- Certification: CE ISO9001
- Minimum Order Quantity: 1 SET
- Price: Negotiable
- Packaging Details: Standard export packaging/customizable packaging
- Payment Terms: T/T L/C



Product Specification

- Highlight: 10 ft microwave parabolic antenna,
13.25 Ghz microwave parabolic antenna,
dual polarized antenna 13.25 Ghz



Product Description

3.0m/10ft Class3 Dual-Polarized Antenna

- Our patent split-lobe microwave communication parabolic antenna for large diameter, which can save packaging and transportation costs greatly without any quality compromised
- High Performance ETSI Class 3 and US FCC 101 compliance parabolic antennas with exceptional front/back ratio – Excellent performance for a wide range of applications
- Simple Assembly – Minimal required assembly simplifies installation on site and guarantees “factory-tested” quality

Electrical performance:

3.0m/10ft ultra high XPD performance dual-polarized microwave parabolic antenna specification

Antenna Model	Antenna Size(m/ft)	Frequency (GHz)	Gain(dBi)			3dB BW (deg)	XPD (dB)	VSWR	F/B ratio (dB)	ISO
			Low	Mid	Top					
CMP303DC	3.0m/10ft	3.6-4.2	38.3	38.9	39.5	1.9	40	1.15	64	45
CMP304DC	3.0m/10ft	4.4-5.0	40	40.6	41.1	1.5	40	1.15	65	45
CMP306WDC	3.0m/10ft	5.925-7.125	42.8	43.6	44.4	1.1	40	1.1	69	45
CMP307WDC	3.0m/10ft	7.125-8.5	44.4	45.2	46.0	0.9	40	1.1	71	45
CMP3010WDC	3.0m/10ft	10-11.7	47.4	48.1	48.7	0.7	40	1.1	73	45
CMP3013WDC	3.0m/10ft	12.2-13.25	49.4	49.6	49.8	0.6	40	1.1	75	45

3.0m/10ft high XPD performance dual-polarized microwave parabolic antenna specification

Antenna Model	Antenna Size(m/ft)	Frequency (GHz)	Gain(dBi)			3dB BW (deg)	XPD (dB)	VSWR	F/B ratio (dB)	ISO
			Low	Mid	Top					
CMP303DB	3.0m/10ft	3.6-4.2	38.3	38.9	39.5	1.9	33	1.15	64	38
CMP304DB	3.0m/10ft	4.4-5.0	40	40.6	41.1	1.5	33	1.15	65	38
CMP306WDB	3.0m/10ft	5.925-7.125	42.8	43.6	44.4	1.1	33	1.1	69	38
CMP307WDB	3.0m/10ft	7.125-8.5	44.4	45.2	46.0	0.9	33	1.1	71	38
CMP3010WDB	3.0m/10ft	10-11.7	47.4	48.1	48.7	0.7	33	1.1	73	38
CMP3013WDB	3.0m/10ft	12.2-13.25	49.4	49.6	49.8	0.6	33	1.1	75	38

3.0m/10ft standard performance dual-polarized microwave parabolic antenna specification

Antenna Model	Antenna Size(m/ft)	Frequency (GHz)	Gain(dBi)			3dB BW (deg)	XPD (dB)	VSWR	F/B ratio (dB)	ISO
			Low	Mid	Top					
CMP303DA	3.0m/10ft	3.6-4.2	38.3	38.9	39.5	1.9	30	1.15	64	35
CMP304DA	3.0m/10ft	4.4-5.0	40	40.6	41.1	1.5	30	1.15	65	35
CMP306WDA	3.0m/10ft	5.925-7.125	42.8	43.6	44.4	1.1	30	1.1	69	35
CMP307WDA	3.0m/10ft	7.125-8.5	44.4	45.2	46.0	0.9	30	1.1	71	35

CMP3010WDA	3.0m/10ft	10-11.7	47.4	48.1	48.7	0.7	30	1.1	73	35
CMP3013WDA	3.0m/10ft	12.2-13.25	49.4	49.6	49.8	0.6	30	1.1	75	35

Mechanical performance:

Diameter of Mounting Pole	Φ114 mm
Fine Azimuth Adjustment	Coarse 360° Fine ±5°
Fine Elevation Adjustment	Fine ±5°
Wind Velocity Operational	180km/h
Wind Velocity Survival	200km/h
Ice-load	25.4 mm
Operational Temperature	-55~ +70

1.The low/mid/high gain has≤-0.5dBi tolerance is within the normal range;

2.F/Bradio:Denotes highest radiation relative to the main beam,at 180°±40°,across the band.Production antennas do not exceed rated values by more than 2 dB unless stated otherwise;



Wuxi Famous Communication Equipment Co., Ltd.



+86 13255118228



eric@mw-antenna.com



mw-antenna.com

Room 803, Wisdom Building, No. 18 Wisdom Road, Huishan Economic Development Zone, Huishan District,
Wuxi City, Jiangsu Province, China